



# TIGER HUMIK

## SECTION 1. IDENTIFICATION

<b>Product Identifier</b>	TIGER HUMIK
<b>Other Means of Identification</b>	Pastillated Sulphur, Humates 4%
<b>Recommended Use</b>	Plant nutrient fertilizer.
<b>Restrictions on Use</b>	Always follow safe handling practices.
<b>Manufacturer/Supplier Identifier</b>	Tiger-Sul Products LLC -Hwy 31 West Industrial Park P.O. Box 5; Atmore, AL; 36504, USA., Tiger-Sul Products LLC -61 Stork Rd; Stockton, CA; 95203, USA. Tiger-Sul (Canada) Co, -275137 Range Road 263 P.O. Box 126; Irricana, AB; T0M 1B0, Canada.
<b>Emergency Phone No.</b>	CHEMTREC, (800) 424-9300 -24 hrs Atmore Toll free, (800) 239-3647 Irricana Toll free, (877) 299-3399

## SECTION 2. HAZARD IDENTIFICATION

Classified according to Canada's Hazardous Products Regulations (WHMIS 2015) and the US Hazard Communication Standard (HCS 2012).

### Classification

Combustible dust - Category 1; Acute toxicity (Dermal) - Category 4; Skin irritation - Category 2; Eye irritation - Category 2A; Skin sensitization - Category 1B; Carcinogenicity - Category 1A

### Label Elements



Danger

May form combustible dust concentrations in air.  
May cause cancer.  
Causes skin and eye irritation.  
May be harmful if swallowed, in contact with skin or if inhaled.

### Other Hazards

None known.

## SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Mixture:

Chemical Name	CAS No.	%	Other Identifiers	Other Names
SULFUR	7704-34-9	84 - 86	EU EINECS/ELINCS Number: 231-722-6	S
BENTONITE	1302-78-9	13 - 15	EU EINECS/ELINCS Number: 215-108-5	CLAY
Humic acids	1415-93-6	4-5		
SILICA, QUARTZ	14808-60-7	0.59 - 0.62	EU EINECS/ELINCS Number: 238-878-4	SiO <sub>2</sub>

## SECTION 4. FIRST-AID MEASURES

### First-aid Measures

#### Inhalation

Take precautions to ensure your own safety before attempting rescue (e.g. wear appropriate protective equipment). Remove source of exposure or move to fresh air.

#### Skin Contact

Avoid direct contact. Wear chemical protective clothing if necessary. Take off contaminated clothing, shoes and leather goods (e.g. watchbands, belts). Wash gently and thoroughly with lukewarm, gently flowing water and mild soap for 5 minutes.

#### Eye Contact

Wear eye protection to avoid dust getting into eyes. If contact and irritation occurs rinse the contaminated eye(s) with lukewarm, gently flowing water for 5 minutes, while holding the eyelid(s) open. Remove contact lenses, if present and easy to do.

#### First-aid Comments

Get medical advice or attention if you feel unwell or are concerned.

### Most Important Symptoms and Effects, Acute and Delayed

If in eyes: may cause moderate to severe irritation. Symptoms include sore, red eyes, and tearing. If on skin: may cause mild to moderate irritation if inhaled: repeated or long term inhalation can cause respiratory problems (SILICA, QUARTZ).

### Immediate Medical Attention and Special Treatment

#### Target Organs

None known.

#### Special Instructions

Treat symptomatically.

Product Identifier: TIGER HUMIK - Ver. 2 April  
Date of Preparation: 15, 2023  
Date of Last Revision: March 1, 2024

SDS No.: 0055

Page 02 of 08

## SECTION 5. FIRE-FIGHTING MEASURES

### Extinguishing Media

#### Suitable Extinguishing Media

Water spray or fog is preferred. If water is not available, use Carbon dioxide, dry chemical powder or appropriate foam. Small fires may be smothered with sand.

#### Unsuitable Extinguishing Media

Avoid scattering spilled material with high pressure water streams.

### Specific Hazards Arising from the Product

Flammable solid.

Combustion products include Sulphur Dioxide and Hydrogen Sulphide.

### Special Protective Equipment and Precautions for Fire-fighters

Wear positive pressure self-contained breathing apparatus (SCBA). Structural firefighters' protective clothing will only provide limited protection.

Chemical protective clothing (e.g. chemical splash suit) and positive pressure SCBA may be necessary. Hydrogen Sulphide is heavier than air and may collect in low lying areas and confined spaces.

## SECTION 6. ACCIDENTAL RELEASE MEASURES

### Personal Precautions, Protective Equipment, and Emergency Procedures

Do not touch damaged containers or spilled product unless wearing appropriate protective equipment. Use the personal protective equipment recommended in Section 8 of this safety data sheet.

### Environmental Precautions

Prevent uncontrolled release to the environment.

### Methods and Materials for Containment and Cleaning Up

Avoid generating dust. Avoid dry sweeping. If necessary, use a dust suppressant such as water. Do not use compressed air for clean-up.

## SECTION 7. HANDLING AND STORAGE

### Precautions for Safe Handling

Avoid breathing in this product. Avoid repeated or prolonged skin contact. Do not get in eyes.

### Conditions for Safe Storage

Store in an area that is: cool, well-ventilated, out of direct sunlight and away from heat and ignition sources.

## SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

### Control Parameters

Chemical Name	ACGIH TLV®		OSHA PEL		AIHA WEEL	
	TWA	STEL	TWA	Ceiling	8-hr TWA	TWA
SULFUR	10 mg/m3		15 mg/m3			
BENTONITE	1 mg/m3	10 mg/m3				
SILICA, QUARTZ	0.025 mg/m3		10 mg/m3			

### Appropriate Engineering Controls

Do not allow product to accumulate in the air in work or storage areas, or in confined spaces. Use local exhaust ventilation, if general ventilation is not adequate to control amount in the air. Provide eyewash in work area, if contact or splash hazard exists.

### Individual Protection Measures

#### Eye/Face Protection

Wear chemical safety goggles.

#### Skin Protection

Wear long sleeved clothing and impervious gloves.

#### Respiratory Protection

For non-routine or emergency situations: wear a NIOSH approved self-contained breathing apparatus (SCBA) or supplied air respirator.

## SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

### Basic Physical and Chemical Properties

<b>Appearance</b>	Dark grey - black pellets. Particle Size: 280SGN
<b>Odour</b>	Not applicable
<b>Odour Threshold</b>	Not applicable
<b>pH</b>	Not available
<b>Melting Point/Freezing Point</b>	115 °C (239 °F) (SULFUR) (melting); Not applicable (freezing)
<b>Initial Boiling Point/Range</b>	Not applicable
<b>Flash Point</b>	207 °C (405 °F) (closed cup) (SULFUR)
<b>Evaporation Rate</b>	Not applicable
<b>Flammability (solid, gas)</b>	Flammable solid. (SULFUR)
<b>Upper/Lower Flammability or Explosive Limit</b>	0.14% (SULFUR) (upper); 0.0035% (SULFUR) (lower)
<b>Vapour Pressure</b>	Not applicable
<b>Vapour Density (air = 1)</b>	Not applicable
<b>Relative Density (water = 1)</b>	Not applicable
<b>Solubility</b>	Insoluble in water; Not available (in other liquids)
<b>Partition Coefficient, n-Octanol/Water (Log Kow)</b>	Not applicable

Product Identifier: TIGER HUMIK - Ver. 2

SDS No.: 0055

Date of Preparation: April 15, 2023

Date of Last Revision: March 1, 2024

Page 04 of 08

<b>Auto-ignition Temperature</b>	232 °C (450 °F) (SULFUR)
<b>Decomposition Temperature</b>	Not available
<b>Viscosity</b>	Not applicable (kinematic); Not applicable (dynamic)
<b>Other Information</b>	
<b>Physical State</b>	Solid
<b>Bulk Density</b>	68.5 lb/ft <sup>3</sup>
<b>Vapour Pressure at 50 deg C</b>	Not applicable

## SECTION 10. STABILITY AND REACTIVITY

### Reactivity

Not reactive under normal conditions of use.

### Chemical Stability

Normally stable.

### Possibility of Hazardous Reactions

None expected under normal conditions of storage and use.

Reacts in the presence of high energy sources (e.g. welding arcs). Dust may cause a fire or explosion.

### Conditions to Avoid

Open flames, sparks, static discharge, heat and other ignition sources.

### Incompatible Materials

Oxidizing agents (e.g. peroxides).

### Hazardous Decomposition Products

Sulphur Dioxide hydrogen Sulfide.

## SECTION 11. TOXICOLOGICAL INFORMATION

### Likely Routes of Exposure

Inhalation; eye contact; skin contact.

### Acute Toxicity

Chemical Name	LC50	LD50 (oral)	LD50 (dermal)
SULFUR	> 0.047 mg/L (rat) (4-hour exposure)	> 5000 mg/kg (rat)	
BENTONITE		5000 mg/kg (rat)	
SILICA, QUARTZ		500 mg/kg (rat)	

0% of the mixture consists of ingredients of unknown toxicity

1222 mg/kg Acute Dermal Toxicity Estimate

### Skin Corrosion/Irritation

May cause irritation to skin, eyes and respiratory tract.

### Serious Eye Damage/Irritation

Can cause serious eye irritation.

### STOT (Specific Target Organ Toxicity) - Single Exposure

#### Inhalation

May cause nose and throat irritation.

#### Skin Absorption

May cause skin to become sensitive to sunlight (ultraviolet light).

#### Ingestion

Product Identifier: TIGER HUMIK - Ver. 2

SDS No.: 0055

Date of Preparation: April 15, 2023

Date of Last Revision: March 1, 2024

Page 06 of 08

May be harmful If large amounts are swallowed

Symptoms may include nausea, vomiting, stomach cramps and diarrhea.

**STOT (Specific Target Organ Toxicity) - Repeated Exposure**

If inhaled: lung injury, irritation of the respiratory system. May cause respiratory tract injury.

N.AV.

**Respiratory and/or Skin Sensitization**

May cause an allergic reaction (skin sensitization) based on limited evidence.

**Carcinogenicity**

If inhaled: lung cancer. A1 – Confirmed human carcinogen. (SILICA, QUARTZ)

**Reproductive Toxicity**

**Development of Offspring**

No information was located.

**Sexual Function and Fertility**

No information was located.

**Effects on or via Lactation**

No information was located.

**Germ Cell Mutagenicity**

No information was located.

**Interactive Effects**

No information was located.

No information was located for: Aspiration Hazard

**SECTION 12. ECOLOGICAL INFORMATION**

Avoid uncontrolled release.

**Ecotoxicity**

**Acute Aquatic Toxicity**

Chemical Name	LC50 Fish	EC50 Crustacea	ErC50 Aquatic Plants	ErC50 Algae
SULFUR	< 14 mg/L (Lepomis macrochirus (bluegill); 96-hour; fresh water; static)	> 5000 mg/L (Daphnia magna (water flea); 48-hour; fresh water; static)		
BENTONITE	19000 mg/L (Oncorhynchus mykiss (rainbow trout); 96-hour; fresh water; static)			

**Chronic Aquatic Toxicity**

Chemical Name	NOEC Fish	EC50 Fish	NOEC Crustacea	EC50 Crustacea
BENTONITE		Not available		

### **Persistence and Degradability**

No ingredient of this product or its degradation products is known to be highly persistent.

### **Bioaccumulative Potential**

This product and its degradation products are not known to bioaccumulate.

### **Mobility in Soil**

If released into the environment, this product is expected to move slowly through the soil, based on physical and chemical properties.

### **Other Adverse Effects**

There is no information available.

## **SECTION 13. DISPOSAL CONSIDERATIONS**

### **Disposal Methods**

Dispose of contents and container in accordance with local, regional, national and international regulations.

## **SECTION 14. TRANSPORT INFORMATION**

Not regulated under Canadian TDG regulations. Not regulated under US DOT Regulations.

### **Environmental Hazards**

Not applicable

**Special Precautions** Not applicable

**Transport in Bulk According to Annex II of MARPOL 73/78 and the IBC Code**

Not applicable

## **SECTION 15. REGULATORY INFORMATION**

### **Safety, Health and Environmental Regulations**

#### **Canada**

This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations and the SDS contains all of the information required by the Controlled Products Regulations.

#### **Domestic Substances List (DSL) / Non-Domestic Substances List (NDSL)**

Listed on the DSL.

#### **USA**

#### **Toxic Substances Control Act (TSCA) Section 8(b)**

All ingredients are listed on the TSCA Inventory.

#### **Additional USA Regulatory Lists**

Listed Pennsylvania Right To Know. (SULFUR)

WARNING: This product can expose you to chemicals including crystalline silica, which is known to the State of California to cause cancer when inhaled. For more information, go to [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov).

This product does not contain any substances regulated as hazardous substances under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302) or the Superfund Amendments and Reauthorization Act (SARA) (40 CFR 355).

Product Identifier: TIGER HUMIK - Ver. 2

Date of Preparation: April 15, 2023

Date of Last Revision: March 1, 2024

SDS No.: 0055

Page 08 of 08

## SECTION 16. OTHER INFORMATION

<b>NFPA Rating</b>	<b>Health - 1</b>	<b>Flammability - 1</b>	<b>Instability - 0</b>
<b>SDS Prepared By</b>	Tiger-Sul		
<b>Phone No.</b>	(877) 299-3399		
<b>Date of Preparation</b>	April 15, 2023		
<b>Date of Last Revision</b>	March 1, 2024		
<b>Key to Abbreviations</b>	ACGIH® = American Conference of Governmental Industrial Hygienists NFPA = National Fire Protection Association NIOSH = National Institute for Occupational Safety and Health OSHA = US Occupational Safety and Health Administration		
<b>Disclaimer</b>	This Safety Data Sheet is offered solely for information, consideration, and investigation purposes. It is not to be construed as recommending any practice or product in violation of any law or regulation. The user is responsible to determine the suitability of the material for use and practice necessary safety precautions. The information presented has been compiled from sources considered to be dependable and is reliable to the best of our knowledge and is not to be considered as a warranty or quality specification.		

---

Product Identifier: TIGER HUMIK - Ver. 2  
Date of Preparation: April 15, 2023  
Date of Last Revision: March 1, 2024

SDS No.: 0055

Page 08 of 08